

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.


**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<p>(51) International Patent Classification ⁶ : H04H 1/00</p>	<p>A1</p>	<p>(11) International Publication Number: WO 95/08226</p> <p>(43) International Publication Date: 23 March 1995 (23.03.95)</p>
<p>(21) International Application Number: PCT/CA94/00505</p> <p>(22) International Filing Date: 15 September 1994 (15.09.94)</p> <p>(30) Priority Data: 2,106,222 15 September 1993 (15.09.93) CA</p> <p>(71) Applicant (for all designated States except US): METEOME- DIA/THE WEATHER NETWORK [CA/CA]; 1755 Rene- Levesque Boulevard East, Montreal, Quebec H2K 4P6 (CA).</p> <p>(72) Inventor; and (75) Inventor/Applicant (for US only): MACKINNON, Russell, D., N. [CA/CA]; 38 St. Paul, Knowlton, Quebec J0E 1V0 (CA).</p> <p>(74) Agent: BERESKIN & PARR; 40th floor, 40 King Street West, Toronto, Ontario M5H 3Y2 (CA).</p>		<p>(81) Designated States: AM, AT, AU, BB, BG, BR, BY, CH, CN, CZ, DE, DK, EE, ES, FI, GB, GE, HU, JP, KE, KG, KP, KR, KZ, LK, LR, LT, LU, LV, MD, MG, MN, MW, NL, NO, NZ, PL, PT, RO, RU, SD, SE, SI, SK, TJ, TT, UA, US, UZ, VN, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG), ARIPO patent (KE, MW, SD).</p> <p>Published</p> <p><i>With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i></p>

(54) Title: A COMMUNICATION NETWORK COMPRISING A PLURALITY OF RECEIVERS WITH USER PROFILE DEPENDENT SELECTION OF PROGRAMMES



(57) Abstract

A communication system comprising: (a) a transmitter having means for transmitting an object stream having one or more objects; (b) a plurality of receivers each including means for receiving said object stream, and each including means for selecting any of said objects from said object stream; (c) means for providing a receiver profile; (d) said receiver profile comprising a list of interest objects for said receiver; and (e) said means for selecting being responsive to said profile for selecting objects from said object stream corresponding to objects of interest.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LU	Luxembourg	TD	Chad
CS	Czechoslovakia	LV	Latvia	TG	Togo
CZ	Czech Republic	MC	Monaco	TJ	Tajikistan
DE	Germany	MD	Republic of Moldova	TT	Trinidad and Tobago
DK	Denmark	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	US	United States of America
FI	Finland	MN	Mongolia	UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				

- 1 -

A COMMUNICATION NETWORK COMPRISING A PLURALITY OF RECEIVERS WITH
USER PROFILE DEPENDENT SELECTION OF PROGRAMMES

Field of the Invention

This invention relates to a communication system. More particularly, the present invention relates to a non-hierarchical network in which receivers are responsive to data objects which are
10 broadcast network wide.

Background of the Invention

In the prior art, there are communications systems for supplying video, audio and data to affiliated receivers in a network for
15 broadcast or display.

These known systems all comprise some form of addressing to identify the destination, i.e. receiver, for the video, audio or data transmission. The addressing scheme produces a single to multi-point network in which communication is provided between a
20 transmitter and one or more receivers.

These known systems have drawbacks. By its very nature, the addressing scheme requires that the transmitter must know the addresses of all the receivers. This implies that the transmitter must have considerable intelligence or processing power. In addition, each
25 receiver must also include sufficient processing power to identify and decode transmissions which are addressed to it. Furthermore, the capacity of the system is dependent on the addressing scheme. Each additional receiver will be seen by the transmitter as an additional address which must be serviced.

30 Therefore, there is a need for a system which provides a communication network in which receivers are responsive to data objects without the need for point-to-point addressing.

SUBSTITUTE SHEET

- 2 -

Brief Summary of the Invention

A feature of the present invention is that the receivers process data independent of the transmitter. The system does not require the transmitter to address any of the receivers. Instead, the
5 transmitter broadcasts a stream of objects and each receiver selects any object according to a local profile.

It is another feature of the present invention that the receivers can provide a number of different services.

In a first aspect, the present invention provides a
10 communication system comprising: (a) a transmitter having means for transmitting an object stream comprising one or more objects; (b) a plurality of receivers each including means for receiving said object stream, and each including means for selecting any of said objects from said object stream; (c) means for providing a receiver profile; (d)
15 said receiver profile comprising a list of interest objects for said receiver; and (e) said means for selecting being responsive to said profile for selecting objects from said object stream corresponding to objects of interest.

Brief Description of the Drawings

For a better understanding of the present invention, and to show more clearly how it may be carried into effect, reference will now be made, by way of example, to preferred embodiments of the present invention shown in the accompanying drawings in which:

25 Figure 1 shows in block diagram form a communication system according to the present invention;

Figure 2 is a detailed block diagram of a receiver for the system shown in Figure 1;

Figure 3 is a functional block diagram showing the
30 primary components of a computer program which controls the operation of the receiver of Figure 2;

Figure 4 is a functional block diagram which shows the

- 3 -

details of a data receptor module for the program of Figure 3;

Figure 5 is a functional block diagram which shows the details of a sequencer module for the program of Figure 3;

Figure 6 illustrates an exemplary profile which is used by
5 the system of Figure 1;

Figure 7 illustrates an exemplary cross-reference table for the profile of Figure 6;

Figure 8 shows the structure of a stream of data objects which is received by the receiver of Figure 2;

10 Figure 9 is a partial listing of an exemplary Sequence List according to the invention;

Figure 10 shows an example "include" file for the Sequence List of Figure 9; and

Figure 11 shows an exemplary Product Definition
15 according to the invention.

Detailed Description of the Preferred Embodiments

Reference is first made to Figure 1 which shows in block diagram form an overview of a communication system 2 according to
20 the present invention. The communication system 2 comprises a communication controller 4, a transmitter 6, a communication channel 8, and a receiver 10 which comprises a communication interface 12 and an on-line de-selector 14.

The communication controller 4 comprises a computer
25 which is coupled to the transmitter 6. The function of the communication controller 4 is to transmit data objects to the receivers 10. For the purposes of the following description, the receiver 10 is coupled to a cable television network 16. As shown in Figure 1, the cable television network 16 comprises a cable television station 18 and
30 cable television subscribers 20 (e.g. households). In the context of a cable television network, the cable television station 18 is a client or user of services which are made available through the

- 4 -

communication network 2. As will be described in detail, the communication network 2 according to the present invention can be used to provide a number of different services, such as weather forecast, stock market reporting, and headline news for example. The
5 cable television station 18 obtains access to these services through the receiver 10 and retransmits the service(s) to the subscribers 20 or households.

In contrast to known systems, the communication controller 4 does not use an addressing scheme, instead the objects are
10 broadcast into space and the receivers 10 accept the data, but only process data objects based on their individual requirements or interests. As will be described in below, an object can comprise digital or computer images, and textual data, related to, but not limited, for example weather, financial or headline news, and the information is
15 transmitted as a stream of data objects. (In addition, as will be described, a live video feed signal and audio signal feed can be incorporated into the service which is provided by the receiver 10.) Each receiver 10 has a profile/scheduler which specifies the objects which are of interest to the receiver 10. The receiver 10 uses its
20 profile/scheduler to "de-select" objects which are of interest to it from the continuous stream of objects existing in space. Because each receiver 10 includes the means for determining which objects it is interested in, the communication controller 4 needs to know very little about the receiver 10, for example, the address or location of each
25 receiver 10 is not required. It will be appreciated by those skilled in the art that this can simplify the design of the communication network.

As shown in Figure 1, the communication controller 4 can include an off-line support module 22. Because the system 2 according to the present invention provides an open network
30 architecture, i.e. receivers 10 existing in space without addresses, the controller 4 need not know much about the receivers 10. The primary task of the controller 4 is providing objects based on the interests of the

- 5 -

users or clients (e.g. the cable television station 18) of the system 2. Therefore, the support module 22 can comprise one or more databases for storing client information and lists of objects for management and inventory purposes. The objects themselves are supplied by an object
5 source 23 and put into a form for transmission (e.g. TIFF format) by an object builder 25 which is coupled to the communication controller 4.

Referring still to Figure 1, the transmitter 6 comprises communication equipment which is coupled to the controller 4. The transmitter 6 provides the interface between the controller 4 and the
10 communication channel 8. The transmitter 6 formats the data objects according to the standard and protocol utilized by the communication channel 8. In the preferred embodiment of the present invention, the communication channel 8 comprises a satellite system. To communicate with the receivers 10, the satellite (communication
15 system 8) uses a signalling channel comprising a baseband signal (which provides the video and audio signal feeds) and includes data sub-carrier, e.g. 512 kiloBaud, for the data objects and another sub-carrier for an audio signal channel. Each of the receivers 10 includes a front-end or communication interface 12 which is compatible with the
20 satellite communication channel 8. In known manner, the transmitter 6 and the front-end of receiver 10 (i.e. communication interface 12) can comprise existing and commercially available satellite communication equipment specified for a baseband channel having for example, a 256 or 512 kiloBaud data sub-carrier.

25 While the following describes a satellite based communication channel 8, however it will be appreciated that any other types of communication links can be utilized for example, optical fiber technology or a high serial modem link over telephone lines.

30 The communication interface 12 (or front-end) in the receiver 10 provides an interface which is compatible with the transmitter 6, as described above. The interface 12 (in the receiver 10)

- 6 -

accepts the incoming satellite signal (baseband video/audio and data sub-carrier) according to the standard and protocol utilized by the transmitter 6 and converts into a signal level which is compatible with the on-line de-selector 14. The communication interface 12 is coupled to the on-line de-selector 14 and supplies the de-selector 14 with a signal comprising a stream of data objects 99 (Figure 8). The incoming signal represents a stream of data objects which are received by all the receivers 10, but processed according to the interests of each receiver 10, as will now be described in detail.

Reference is next made to Figure 8 which shows the organization of a stream of data objects 99. As shown, the stream 99 comprises a series of data objects denoted generally by reference 100. Each object 100 comprises an object data portion 102 which contains data or information related to the service being provided, for example, video images for a headline news story. In addition to the data portion 102, the object 100 includes a start of object field 104, an object sequence number 106, an object identifier field 108 which comprises a Unique ID, a time stamp field 110, and an associated service field 112, and an end of object field 114.

The start of object field 104, the end of object field 114 and the object sequence number 106 are part of the overhead information required to transmit and receive the object 100 as will be understood by one skilled in the art. The start of object and end of object fields 104,114 define the start and end of a data object 100, and can include error detection information such as a checksum or CRC code.

There may be instances where the information being transmitted, e.g. news video images, exceed the capacity of the object data portion 102. In such cases the object data 102 can be transmitted as a sequence of objects 100 and the object sequence number field 106 is used to define the object number in the sequence.

Referring still to Figure 8, the Unique ID field 108 contains a name or identifier which allows the object 100 to be identified by the

- 7 -

receiver 10 and selected if the object 100 is of interest as determined by the profile (see below). Because the data portion 102 defines what the object is, the Unique ID field 108 can simply contain a generic name to identify the object 100. This feature also allows the system 2 to use a single stream 99 to provide many different types of services, e.g. weather forecasting and headline news.

The time stamp field 110 is included because certain types of objects, e.g. weather forecast, can become obsolete after a certain time. The time stamp field 110 comprises date and time of day information that indicates when the object 100 was created. The time stamp 110 can be assigned by the object builder 25 (Figure 1). As will be described below, the receiver 10 can use the time field 110 as a criterion for selecting objects 100 from the stream of objects 99. For example, an older object 100 can be replaced by a newer object, as determined by the time stamp 110.

Referring again to Figure 8, the associated service field 112 identifies the service with which the object is associated, for example, a headline news service or a stock market service.

As introduced above, the receiver 10 uses its profile/scheduler to "de-select" objects 100 (Figure 8) which are of interest to it from the continuous stream of objects 99 existing in space. An exemplary profile 120 is shown in Figure 6. The profile 120 is a record for the receiver 10 which contains specific information 122 and service specific information 124. The profile 120 can reside on a diskette (not shown) or be burned into an EPROM (not shown) which is read by the receiver 10. Alternatively the profile 120 can be entered into memory in the receiver 10 via a serial port connection 15 which couples the receiver 10 to a local off-line support module 17 (Figure 1). The primary function of the off-line support module 17 is to give the cable station 18 the capability to modify or augment the profile 120.

The principle function of the profile 120 is to provide the receiver 10 with information so that the receiver 10 can determine

- 8 -

which objects 100 in the stream of objects 99 are of interest to it and therefore should be selected from the stream 99. The profile 120 is originally generated by compiling the interests of a cable television station 18, for example by completing a questionnaire. The interests
5 are then compiled into a profile 120 for that station. The profile 120 is then forwarded to the station 18, in the form of diskette for example, and installed in the receiver 10.

As shown in Figure 5, the receiver 10 specific information comprises a time zone designation 126, a daylight saving offset
10 designation 128, a daylight saving date and time zone designation 130, and a language designation 132.

The information in the daylight saving date designation 130 is used by the receiver 10 to determine when to activate/deactivate daylight savings time.

15 As described above, the objects 100 in the stream 99 can have more than one language. The receiver 10 uses its language designation 132 to determine its language, i.e. the language of objects that it is interested in. For example, a French designated receiver 10 will only select those objects 100 which have an object identifier 108
20 which implicitly signifies an object in the French language.

Referring still to Figure 6, the service specific information 124 comprises two general types of elements: system resource allowances 134 and an object cross-reference table 136. The receiver 10 uses the system resource allowances information 134 to configure its
25 resources for the service to be provided, e.g. memory allocation. The object cross-reference table 136, on the other hand, lists the objects that are associated with a service, provides the selection criteria by which the receiver 10 will select the objects 100 from the object stream 99 (Figure 8), and also provides a local or Internal ID for use by the
30 receiver 10.

In the receiver 10, the objects 100 can be identified according to their Unique ID 139 contained in field 108 (Figure 8) of the

- 9 -

packet 100. The objects 100 can also be renamed with a corresponding Internal ID 140 which is contained in the object cross-reference table 136 as shown in Figure 7. The cross-reference table 136 is preferred because it provides an "anti-collision" feature which is described
5 below.

The cross-reference table 136 shown in Figure 7 comprises a list of "Unique ID" object identifiers 138 which are unique to the entire communication network. The cross-reference table 136 also includes a list of "Internal ID" object identifiers 141 for use in the
10 receiver 10. The receiver 10 uses the Unique ID 139 to identify objects which are of interest to it. An object of interest is retained by the receiver 10 and then renamed according to the corresponding Internal ID 140. By renaming the object internally, the receiver 10 can avoid overwriting the object with a newly received object with the same
15 Unique ID 139. Thus, the cross-reference table 136 can provide an "anti-collision" function. The cross-reference table 136 can also be used to maintain compatibility between older versions of receivers 10.

As described above with reference to Figure 6, the service specific portion 124 of the profile 120 defines a "list of objects" which
20 are of interest to the receiver 10. In the alternative, the "list of objects" can be determined or calculated according to an algorithm in the receiver 10. For example, the algorithm can operate on data taken from the unit specific information 122 or a play-list for the receiver 10. According to this embodiment of the invention, the algorithm
25 produces a list of objects which are of interest to the receiver 10 thereby the receiver 10 the capability to determine its own profile 120.

Reference is next made to Figure 2 which shows the structure of the on-line de-selector 14. The on-line de-selector 14 comprises a communication board 24 and a graphics display board 26
30 which are coupled to a central processing unit module 28 through a bus 30. The on-line de-selector 14 is based on the well-known ISA or PC-AT (trademark) bus architecture. The central processing unit 28

- 10 -

executes an application program which controls the operation of the on-line de-selector 14. In the preferred embodiment, the central processing unit 28 module comprises an Intel 286/386/486 or Pentium (trademark) type microprocessor, a clock with battery backup, random
5 access memory (1 megabyte minimum), and read only memory (not shown). The central processing module 28 can include other resources, such as DMA (Direct Memory Access) controller (not shown).

The role of the communication board 24 is to extract objects 100 from the incoming data object stream 99 (Figure 7) which
10 are of interest to the receiver 10. The function of the display board 26 is to display the objects which have been selected from the object stream by the communication board 24. The objects 100 are extracted according to the profile 120 which defines the interests of the receiver 10 (see Figure 6). The interests of the receiver 10, in turn, are
15 determined by the client or user, e.g. the services that the cable television station 18 will provide its subscribers 20. Because the receiver 10 knows what objects it wants, the central communication controller 4 does not need to know this, and therefore the need for addressing the receivers 10 for selected data transfer is eliminated.

20 As shown in Figure 2, the communication board 24 comprises a digital module 34. The digital module 34 is coupled to an integrated receiver demodulator 32 which is located upstream of the on-line de-selector 14, for example in the communication interface 12. The function of the IRD module 32 is to descramble the incoming
25 baseband signal from the receiver 10 and apply error detection and correction to the incoming signal. The IRD module 32 demodulates and decompresses the baseband video signal, the audio sub-carrier and the data sub-carrier to recover the data object stream 99 (Figure 8). Once the data sub-carrier has been demodulated, the module 32 can
30 apply known error detection and correction techniques. The IRD module 32 includes a data output 38 which is coupled to the digital module 34 and supplies serial digital data, e.g. the object stream 99.

- 11 -

The IRD module 32 also includes an audio feed output 36 and a video feed output 37. The implementation of the IRD module 32 is within the understanding of those skilled in the art and comprises a known product which is available from Scientific Atlanta for example.

5 As described above, the digital module 34 receives and processes a serial digital feed 38. The digital module 34 can be implemented using the known HDLC/SDLC communication protocol and error correction techniques and the Intel 82530 family of communication processor.

10 In known manner, the IRD module 32 can be packaged on an AT-style board which plugs into a slot on the ISA bus. If the communication channel 8 is not a satellite link, then the IRD module 32 can be replaced according to the communication protocol being used, for example, a high speed serial digital stream over an optical
15 fiber link.

Referring still to Figure 2, the primary function of the digital module 34 is to extract or deselect objects 100 from the received object stream 99 based on the particular interests (i.e. profile 120) of the receiver 10. This function is implemented in the form of a computer
20 program which is described below. The digital module 34 also provides buffering for the demodulated data objects.

The digital module 34 can be located on another AT-style board. Partitioning the IRD module 32 and the digital module 34 allows the IRD or analog module 32 to be changed (e.g. for a different
25 communication interface) without changing the digital module 34. Communication between the IRD and digital modules 32,34 is accomplished through the serial link 38 as shown in Figure 2. Alternatively, the digital module 34 can be implemented as a software function in the computer program which is executed by the central
30 processing unit 28.

As shown in Figure 2, the display board 26 is also coupled to the ISA bus 30. The function of the display board 26 is to provide the

- 12 -

objects that have been selected by the digital module 34 in a form (e.g. as cable television video signals) which is suitable for consumption by the user or client (e.g. cable television station 18). If the data portion 102 of the objects 100 are transmitted in a compressed format (e.g. TIFF
5 - Tagged Image File Format using packed bit compression), the objects must be decompressed.

The display board 26 includes a raster module 40. The raster module 40 includes memory which is used to store and process objects containing video images. According to the invention, there are
10 two planes of raster memory: the main raster having at least two pages; and the overlay plane. The display board 26 processes its own Vertical Blanking Interval (VBI) interrupt. The display board 40 preferably has the following functionality: (a) 256/32768 colour display; (b) display resolution of 640 x 480 for NTSC based television systems;
15 (c) 768 x 576 display resolution for PAL based television systems; (d) a text function; (e) switching between three video inputs (i.e. video signal feed, computer image or video feed signal overlaid with a computer image); (f) overlaying of the video feed signal with a computer image; (g) decompressing images, e.g. RLE or LZW; and (h)
20 display of time of day clock. This functionality can be provided using known technology as will be within the understanding of one skilled in the art. The display board 26 can also be packaged on an AT-style board which plugs into the ISA bus 30 and runs under the control of the central processing unit 28.

25 The on-line de-selector 14 also includes an audio module 42 which is used to process objects having audio information. The audio module 42 preferably includes the capability to switch between audio inputs, for example, the audio feed 36 provided by the IRD module 32 and a local audio feed.

30 Referring still to Figure 2, the processing resources of the on-line can be augmented by peripheral boards 44. The peripheral boards 44 which plug into the ISA bus 30 can comprise additional

- 13 -

memory (e.g. RAM and/or Flash Disk) to increase the capacity of the receiver 10, or a fax/modem board for example.

Reference is next made to Figure 3 which shows in functional block diagram form an application program 50 executed by the receiver 10 according to the present invention. The application program 50 is based on a micro-kernel real-time operating system for example the commercially available QNX (trademark) system known to one skilled in the art. The program 50 comprises a number of tasks running simultaneously under different priorities. As shown in Figure 3, the application program 50 comprises seven functional modules: a data receptor module 52; a profile manager 54; a system monitor module 56; a series of service modules 58a to 58n; a series of graphic board software modules 60a to 60n; a "heartbeat" module 62; a utilities module 64 and a start-up module 66.

Referring to Figure 3, the system monitor 56 comprises a set of functions which manage the operation of the program 50, such as the queuing of tasks performed by the various modules described below.

The heartbeat module 62 synchronizes the receiver 10. According to the invention, the receivers 10 in the system 2 are not under real time control of the communication controller 4, however, the communication controller 4 sends a heartbeat packet periodically which is used by the receivers 10 to synchronize. The heartbeat packet indicates what the Greenwich Mean Time (GMT) will be at the next vertical blanking interval (VBI). Each receiver 10 receives the GMT update and converts it to local time according to its geographic location which can be determined from the profile 120. The program 50 can use the local time to produce a time of day display for the overlay plane.

The utilities module 64 provides a series of utility tasks and drivers. For example, the utilities module 64 can include a self-diagnostics function and the software interface for the off-line support

- 14 -

module 17 (Figure 2), or the software interface for supporting a fax modem board.

The data receptor module 52 processes the incoming object data stream 99 (Figure 8). The data receptor module 52 serves as the interface to the communication processor 24 (Figure 2). The data receptor module 52 controls the operation of the digital module 34 (Figure 2) to perform the following operations: (a) assembling objects (e.g. a video image corresponding to an object may be transmitted in a sequence of packets); (b) buffering the objects for the display processor 26 (Figure 2); and (c) routing, i.e. dispatching, the objects to the appropriate display processor 26 (Figure 2). As shown in Figure 3, the data receptor 52 is coupled to the profile manager 54 which provides access to the profile 120 in order to select and assemble the objects of interest to the receiver 10. The data receptor module 52 is shown in more detail in Figure 4 and described below.

Referring to Figure 3, the start-up module 66 initializes the receiver 10 when power is first applied or if there is a reset, either hardware or software. The receiver 10 uses the start-up module 66 to "boot" from an electronic storage device, e.g. floppy or hard disk drive, which contains all the required software and data, e.g. program 50 and profile 120, to initialize the receiver 10.

Once the receiver 10 is initialized, the program 50, i.e. data receptor 52, waits for the object stream 99 to be broadcast by the communication controller 4 and transmitter 6. The communication controller 4 broadcasts the object stream 99 to all the receivers 10 in the system 2. Each receiver 10 receives the object stream 99 and then decides which objects 100 are of use or interest to it. The program 50 then uses one of the service modules 58a to 58n to display the objects of interest e.g. weather service or headline new service.

Referring to Figure 3, each of the services modules 58a to 58n comprises a sequencer 59a to 59n and a graphics driver 61a to 61n. The sequencer module 59a to 59n is a software function which displays

- 15 -

the objects stored by the data receptor 52 according to a "play or sequence list". The sequence-list defines the objects to be displayed and their respective start times. Figure 9 shows a partial sequence list and is described below.

5 The graphics driver module 61a to 61n provides an interface between the sequencer 59a to 59n and the graphics board software 60a to 60n. In its simplest form, the graphics driver module 61a generates the "handshaking" required for passing object data to the graphics board 26 (Figure 2) for video display.

10 Referring next to Figure 4, the data receptor module 52 comprises a communications driver 68, an object assembler 70 and a cross-referencer 72. The communications driver 68 provides the interface to the object data stream 99 which is inputted by the communications board 26. The communications driver 68 allows the
15 receiver 10 to be independent from the form of the communication channel or medium 8. The communications driver 68 can be implemented based on known communication protocols, such as SDLC/HDLC protocol using an Intel 82530 communication chip (not shown) operating at 256 (or 512) KiloBaud or a serial communication
20 protocol operating at 19.2 KiloBaud. The primary functions performed by the communication driver 68 are to receive each frame or packet in the object stream 99; to detect errors in the received frame or packet; and if possible replace any corrupted frames. Once a complete packet 99 is received, the communication driver 68 forwards it to the next task,
25 i.e. the object assembler 70.

 The primary function of the object assembler 70 is to either "flush" or keep the data block in the data stream 99 comprising the object 100. If the object is of interest to the particular receiver 10, then the data block is written to a mass storage device 74, e.g. a hard
30 disk, which comprises an "object repository". If the object 100 is not of interest, the object assembler 70 "flushes" the data block. The object assembler 70 uses the profile manager 54 to access the Profile 120

- 16 -

(Figure 6) which is stored locally to determine if an object is of interest. The Profile 120 contains a list of Object ID's which are of interest. Because the objects are transmitted to all the receivers 10 in the field, every piece of information comprises an object with a Unique ID. The
5 object assembler 70 only looks at the Unique ID of the object 100 and is not concerned with the content of the object, therefore the object can comprise any type of file.

Objects 100 which are of interest to the receiver 10 are renamed with an Internal ID 140 (Figure 7) from the cross-referencer
10 72. The Internal ID is used as a collision avoidance function to ensure that an object which is received does not overwrite or replace an object which is currently being displayed. To this end, the principal functions performed by the cross-referencer 70 are to rename the object from its UniqueID to its Internal ID; to ensure that there is no overlap between
15 Internal ID assignments (i.e. "internal collisions"); and to send notification of Internal ID assignment to any other functions as required. The cross-referencer 70 accesses the cross-reference table 136 as shown in Figure 7.

The object repository on the mass storage device 74
20 comprises a directory which is used to access the objects that have been selected by the receiver 10. The directory is part of a file system which lists the objects that were selected by the data receptor 52 (see above). In the structure of the directory and file system is implemented according to the real time operating system (see above), for example, QNX
25 (trademark) platform.

Reference is next made to Figure 5 which shows the sequencer module 59 in more detail. The sequencer module 59 is a function which operates on the objects 100 in order to produce a service which has been requested by the user or client, e.g. the cable
30 television station 18 and related to the service provider 58. For example, there can be a service provider 58a for a headline news service, a service provider 58b for the financial markets, a service

- 17 -

provider 58c for sports headline, and a service provider for weather reports 58n. If the client has subscribed to a headline news service, the sequencer module 59a will perform the tasks required to display headline new stories. These tasks can involve displaying video images accompanied by audio to report the news, for example. In addition, a text message crawling along the bottom of the image can also be provided. The service to be provided defines the type of video images and the audio information which are produced by the receiver 10, and the objects associated with a service define the content of the video images and audio information.

A feature of the system 2 according to the present invention is that the object driven receivers 10 combined with the service modules 58a to 58n allow the a receiver 10 to distribute many services from a single source.

As shown in Figure 5, the sequencer module 59 comprises a sequencer task 76, a raster display task 78, and an overlay display task 80. The sequencer 76 is a function which displays the stored objects according to a sequence-list 77. The function of the sequencer 76 is to assemble (and display) the objects 100 stored in the object repository 74 according to the sequence-list or play-list 77.

As shown in Figure 9, the sequence-list 77 defines the data, i.e. objects 100, to be displayed for a service, e.g. headline news, and their respective start times. Each operation in the sequence list 77 either comprises an "#include" command or a "#display" command according to the QNX platform. The sequencer 76 uses #include command to include or retrieve another file and the #display command to display data. As shown in Figure 9, each entry in the sequence list 77 includes a command field 150, a start time 152, an end time 154 and a parameter field. The command field 150 specifies whether the entry is an #include or a #display command. The sequences are coded as using a count of seconds starting Sunday morning at 0000:00:00 for example. As described above, the heartbeat

- 18 -

packet synchronizes the receiver 10 with the communication controller 4. To execute an entry in the sequencer list 77, the sequence 76 compares the start and end time fields 152,154 to the current time in the receiver 10 and executes the entry if the current time is within the defined range. If synchronization is lost, then the sequencer 76 executes a default sequence until synchronization is established. Because the start and end time fields 152,154 are specified, it is not necessary for the sequencer 76 to open the file and therefore the sequencer 76 can quickly regain synchronization.

10 The parameter field 156 provides additional parameters which are needed to execute the operation. For example, the parameter field 156 includes a sub-field 158 for specifying the video source, e.g. V1; a sub-field 160 for the raster plane, e.g. R; a sub-field 162 for the overlay plane, i.e. O; a sub-field 164 for the time of day clock, i.e. C; and a sub-field 166 for the product definition name, e.g. 0102. In the case of an "#include" command, the parameter field 156 contains the name of a file to be included, e.g. "mprev100aov.seq" as shown in Figure 10.

20 The objects 100 to be displayed by the sequencer 76 can be displayed either on the raster plane and/or on the overlay plane of the graphics image as will be understood by those skilled in the art. The two sub-fields 160,162 define which planes are to be used.

25 The raster display task 78 receives messages from the sequencer 76 and performs the operations necessary for display on the "raster plane". The raster display task 78 includes a product definition file 82 which tells the raster task 78 what layers comprise the image to be displayed on the raster plane. Figure 11 shows eight examples of product definitions 168 to 182. The first line, i.e. 00, of each product definition contains the product definition number, for example "0102" for product definition 174. Each line in the definition 174 can also include a description or comment. The remaining lines, i.e. 01, in the definition 174 comprise the layers which together form a composite

30

- 19 -

image to be displayed on the raster plane. Each line 01 includes a file name, e.g. SL231.TGA which contains the data for the layer. The files can include data which was received from the communication controller 4 through the object stream 99. The raster task 78 reads the
5 data from the files, e.g. SL231.TGA, associated with the product from disk 74 and sends it to the graphics display board 26. The product definition 174 also includes a parameter field 175 which provides additional information for processing the layer. For example, the parameter field 175 can specify whether an layer is to decompressed in
10 OPAQUE or TRANSPARENT form. Unlike known systems, the receiver 10 according to the present invention has no capability to generate graphics, e.g. line, shape or text drawing. According to the invention, the images are built from a series of layers which are decompressed on the graphics display board 26.

15 In the event that there is fault with the required image, the raster task 78 includes the capability to display a default slide or image. This can be specified in the technical parameter field 175.

The overlay display task 80 receives messages from the sequencer task 76 and handles the display in the "overlay plane". The
20 overlay task 80 also includes a product definition file 84 stored on disk. In response to commands from the sequencer 76, the overlay task 80 assembles the layers comprising the image according to the product definition 84 and passes the compressed data to the graphics display board 26 through the graphics driver module 61. The actual display
25 and presentation of the objects is provided by the graphics board 26 under the control of the graphics board software 60.

As described above, the sequencer 76 performs the actions described by issuing a sequence of instructions to the graphics display board 26 through the raster task 78 and the overlay task 80 according to
30 the sequence list 77. The sequence 77 includes a series of "#include" files which can contain other include or display instructions.

In operation, the sequencer 76 sequences through a list of

- 20 -

display operations while keeping in synchronization with the internal clock generated by the heartbeat module 62. As required, the sequencer 59 sends messages to the raster and overlay tasks 78,80 which prepare the desired images, i.e. products, for display by the graphics display board 26. The sequencer 76 also includes the capability to operate under exception conditions. The exception conditions include loss of synchronization with the communication controller 4; loss of Genlock; or a sequence file is missing. The exception condition can also include a special warning or advisory which is issued by the communication controller 4 for a particular service, e.g. weather service.

The receiver 10 according to the present invention operates as a "slide machine" and the end result of the service module 58 is to produce a video output and/or audio signal output for the service (e.g. headline news), which can be retransmitted by the cable television station 18 to the households 20 in the cable network 16.

Although various preferred embodiments of the present invention have been described in detail, it will be appreciated by those skilled in the art, that variations may be made without departing from the spirit of the invention or the scope of the appended claims.

- 21 -

I CLAIM:

1. A communication system comprising:
 - 5 (a) a transmitter having means for transmitting an object stream comprising one or more objects;
 - (b) a plurality of receivers each including means for receiving said object stream, and each including means for selecting any of said objects from said object stream;
 - 10 (c) means for providing a receiver profile;
 - (d) said receiver profile comprising a list of interest objects for said receiver; and
 - (e) said means for selecting being responsive to said profile for selecting objects from said object stream
15 corresponding to objects of interest.
2. The communication system as claimed in claim 1, wherein said receiver comprises a communication port and an on-line de-selector, said communication port including said means for
20 receiving said object stream and said on-line de-selector including said means for selecting.
3. The communication system as claimed in claim 1 or 2, wherein said means for providing a receiver profile comprises a
25 diskette.
4. The communication system as claimed in claim 2, wherein said on-line de-selector includes data reception means for receiving data from said communication port, and said data reception
30 means having means for accessing said receiver profile.
5. The communication system as claimed in claim 4,

- 22 -

wherein said means for accessing said receiver profile comprises a profile manager.

6. The communication system as claimed in claim 4,
5 wherein said data reception means comprises a communications driver and an object assembler, said communications driver having means for interfacing said data reception means to said communication port and said object assembler being coupled to said communications port and having means for receiving said object
10 stream and including selection means responsive to said receiver profile for selecting objects from said object stream according to said list of interest objects.

7. The communication system as claimed in claim 6,
15 wherein said data reception means includes storage means for storing said selected objects for retrieval.

8. The communication system as claimed in claim 6,
wherein said selection means comprises means for reading a name for
20 said object and comparing said name to said list of objects.

9. A receiver for use in a communication system for receiving data, said receiver comprising:

- 25 (a) receiver means for receiving said stream of data and said data comprising one or more objects;
- (b) selection means for selecting any of said objects from said data;
- (c) means for providing a receiver profile having a list of objects of interest to said receiver; and
- 30 (s) said selection means being responsive to said profile for selecting objects from said data corresponding to objects of interest to said receiver.

- 23 -

10. The communication system as claimed in claim 9, wherein said receiver includes means for generating images from said selected objects.

5 11. The communication system as claimed in claim 9, wherein said means for providing a receiver profile comprises a diskette.

10 12. The communication system as claimed in claim 1, 9 or 11, wherein said object stream comprises data objects associated with a weather forecast service.

13. The communication system as claimed in claim 1, 9 or 11, wherein said object stream comprises objects associated with a
15 headline news service.

14. The communication system as claimed in claim 1, 9 or 11 wherein said object stream comprises objects associated with a sports headline service.

15. The communication system as claimed in claim 1, 9 or 11 wherein said object stream comprises objects associated with a financial market reporting service.




FIG. 1

2/8




FIG. 2

SUBSTITUTE SHEET

3/8






FIG. 3



SUBSTITUTE SHEET.

4/8

FIG. 4FIG. 5

SUBSTITUTE SHEET

5/8

FIG. 6FIG. 7

6/8




FIG. 8

SUBSTITUTE SHEET

7/8

150	152	154	158	160	162	164	166
#DIS	S000:00:00	000:00:03	V1	R-	O-	C-	0102
#INC	S000:00:03	000:00:10	ma.seq				156
#DIS	S000:00:10	000:00:40	V1	R-	O-	C-	
#INC	S000:00:40	000:01:40	mprev100aov.seq				
#DIS	S000:01:40	000:01:50	V1	R-	O-	C-	
#DIS	S000:01:50	000:03:30	V1	R-	O1	C1	
#DIS	S000:03:30	000:04:00	V1	R-	O-	C-	
#INC	S000:04:00	000:04:15	mscrollregobs.seq				
#DIS	S000:04:15	000:04:25	V1	R-	O-	C-	
#DIS	S000:04:25	000:06:05	V1	R-	O1	C1	
#DIS	S000:06:05	000:10:45	V1	R-	O-	C-	
#INC	S000:10:45	000:11:45	mprev100aov.seq				
#DIS	S000:11:45	000:12:45	V1	R-	O-	C-	
#DIS	S000:12:45	000:12:55	V1	W			
#DIS	S000:12:55	000:13:50	V1	R-	O1	C1	
#DIS	S000:13:50	000:14:00	V1	R-	O-	C-	
#DIS	S000:14:00	000:14:29	V1	R-	O1	C1	
#DIS	S000:14:29	000:15:50	V1	R-	O-	C-	
#DIS	S000:15:50	000:17:50	V1	R-	O1	C1	
#DIS	S000:17:50	000:20:03	V1	R-	O-	C-	
#INC	S000:20:03	000:20:10	ma.seq				
#DIS	S000:20:10	000:20:40	V1	R-	O-	C-	
#INC	S000:20:40	000:21:40	mprev100aov.seq				
#DIS	S000:21:40	000:21:50	V1	R-	O-	C-	
#DIS	S000:21:50	000:22:45	V1	R-	O1	C1	
#DIS	S000:22:45	000:23:30	V1	W			
#DIS	S000:23:30	000:24:00	V1	R-	O-	C-	
#INC	S000:24:00	000:24:15	mscrollregobs.seq				
#DIS	S000:24:15	000:24:25	V1	R-	O-	C-	
#DIS	S000:24:25	000:26:05	V1	R-	O1	C1	
#DIS	S000:26:05	000:29:00	V1	R-	O-	C-	
#INC	S000:29:00	000:29:14	mpollen.seq				
#DIS	S000:29:14	000:30:20	V1	R-	O-	C-	
#INC	S000:30:20	000:31:20	mprev100aov.seq				
#DIS	S000:31:20	000:32:00	V1	R-	O-	C-	
#DIS	S000:32:00	000:33:29	V1	R-	O1	C1	
#DIS	S000:33:29	000:35:50	V1	R-	O-	C-	
#DIS	S000:35:50	000:37:50	V1	R-	O1	C1	
#DIS	S000:37:50	000:40:03	V1	R-	O-	C-	
#INC	S000:40:03	000:40:10	ma.seq				
#DIS	S000:40:10	000:40:40	V1	R-	O-	C-	
#INC	S000:40:40	000:41:40	mprev100aov.seq				
#DIS	S000:41:40	000:41:50	V1	R-	O-	C-	
#DIS	S000:41:50	000:43:30	V1	R-	O1	C1	
#DIS	S000:43:30	000:44:00	V1	R-	O-	C-	
#INC	S000:44:00	000:44:11	mscrollregobs.seq				
#DIS	S000:44:11	000:44:15	RP				
#DIS	S000:44:15	000:44:25	V1	W			
#DIS	S000:44:25	000:45:55	V1	R-	O1	C1	
#DIS	S000:45:55	000:51:15	V1	R-	O-	C-	
#INC	S000:51:15	000:52:15	mprev100aov.seq				
#DIS	S000:52:15	000:52:55	V1	R-	O-	C-	
#DIS	S000:52:55	000:53:50	V1	R-	O1	C1	
#DIS	S000:53:50	000:54:00	V1	R-	O-	C-	
#DIS	S000:54:00	000:54:29	V1	R-	O1	C1	
#DIS	S000:54:29	000:55:50	V1	R-	O-	C-	
#DIS	S000:55:50	000:57:50	V1	R-	O1	C1	
#DIS	S000:57:50	000:58:30	V1	R-	O-	C-	
#DIS	S000:58:30	000:59:54	V1	W			

FIG. 9

77

SEQUENCE LIST

8/8

; mprev100acv.seq

```

;
#DIS      S000:00:00      000:00:12      V1      RT      01      C1
#DIS      S000:00:12      000:00:24      V1      RT      PTYSS$StS2PCPL1_MM
#DIS      S000:00:24      000:00:36      V1      RT      PTYSS$StS3PCPL1_MM
#DIS      S000:00:36      000:00:48      V1      RT      PTYSS$StSYSNSN1_MM
#DIS      S000:00:48      000:00:56      V1      RT      O- C- PTYSS$StSYSLSL1
#DIS      S000:00:56      000:01:00      RP      PTYSS$StS1PCPL1_MM

```

SEQUENCE FILE INCLUDED IN SEQUENCE LIST (FIG. 9)

FIG. 10

; This file is a portion of the product definition file

```

00      0000      ...      "Un Moment S.V.P."
01      SL000.TGA      ...      Logo MM
02      SL001.TGA      ...      "Un Moment S.V.P."

00      0100      ...      Observations Automatiques
01      SL011.TGA      ...      Fond Opaque 3 Zones
01      SL101.TGA      ...
01      SL201.TGA      ...
01      SL253.TGA      ...
01      SL300.TGA      ...

00      0101      ...      Observations Manuelles
01      SL011.TGA      ...      Fond Opaque 3 Zones
01      SL211.TGA      ...
01      SL311.TGA      ...

00      0102      ...      Conditions Locales - Page 1
01      SL231.TGA      ...      Fond Opaque 3 Zones
01      SL202.TGA      ...
01      SL302.TGA      ...
01      SL322.TGA      ...
01      SL324.TGA      ...

00      0203      ...      Conditions Locales - Page 2
01      SL233.TGA      ...      Fond Opaque 3 Zones
01      SL234.TGA      ...
01      SL235.TGA      ...

00      0404      ...      Conditions Locales - Page 3
01      SL232.TGA      ...      Fond Opaque 3 Zones
01      SL444.TGA      ...
01      SL445.TGA      ...

00      0511      ...      Statistiques
01      SL551.TGA      ...      Fond Opaque 3 Zones
01      SL552.TGA      ...

00      0606      ...      Phases de la Lune
01 -    SL611.TGA      ...      Fond Opaque 3 Zones

```

; Note: The dots "..." indicate technical parameters.

SUBSTITUTE SHEET

INTERNATIONAL SEARCH REPORT

International application No.
PCT/CA 94/00505

A. CLASSIFICATION OF SUBJECT MATTER
IPC 6 H04H1/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 6 H04H

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP,A,0 190 837 (THORN EMI FERGUSON LTD.) 13 August 1986	1,9,10
A	see page 1, line 1 - page 4, line 2; claims 1-4; figures 1,3 ---	7
X	CH,A,665 516 (MARCEL MÜLLER) 13 May 1988 see page 2, column 1, line 55 - column 2, line 30; claims 1,3 ---	1,9,12, 15
A	GB,A,2 256 346 (ALI GURYEL) 2 December 1992 see page 1, line 1 - page 2, line 21; claims 1,3,4,6,8,13; figure 1 --- -/--	13

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *Z* document member of the same patent family

Date of the actual completion of the international search

23 December 1994

Date of mailing of the international search report

13.01.95

Name and mailing address of the ISA

European Patent Office, P.O. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 cpo nl,
Fax: (+31-70) 340-3016

Authorized officer

De Haan, A.J.

INTERNATIONAL SEARCH REPORT

International application No.

PCT/CA 94/00505

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	DE,A,39 09 334 (PFEIFER, WERNER) 20 September 1990 see column 1, line 1 - column 3, line 33; claim 1; figure 1 -----	1,9

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No.
PCT/CA 94/00505

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP-A-0190837	13-08-86	NONE	
CH-A-665516	13-05-88	NONE	
GB-A-2256346	02-12-92	NONE	
DE-A-3909334	20-09-90	NONE	